





VRE-12G2

Specifications	The Vector VRE-12G2 is the ideal audio solution for users requiring a passive speaker system. With a power rating of 800W, the VRE-12G2 offers plenty of headroom when connected to a power amplifier. The twist lock input/output sockets ensure that cables are held securely when connected. All encased within a lightweight ABS moulded enclosure with 3 carry handles and 35mm pole stand socket.
Model	VRE-12G2
Description	VECTOR by HH VRE-12G2 - Passive moulded speaker - 800W - 12 inch LF + 1 inch CD
Power Rating	200W RMS, 800W Peak
Impedance	8 ohm
HF Driver	1" Compression Driver
LF Driver	12" Woofer
Sensitivity (1W/1M)	96
Coverage	90°H X 40°V
Enclosure	
Cabinet	Robust polypropylene cabinet with three handles and monitor angle
Finish	Black
Grille	Powdercoated steel, Black with acoustic foam backing
Other	35mm Distance Pole Socket Socket
Unit dimensions (HWD)	58.5 x 36.5 x 32.5 CM 23" x 14.4" x 12.8"
Unit weight	8.3Kg, 18.3 lbs
Carton dimensions (HWD)	65.8 x 43.5 x 36 CM 25.9" x 17.1" x 14.2", 0.103 M3 11Kg, 24.3 lbs 5060109456820
Packed weight	11Kg, 24.3 lbs
EAN Code	5060109456820
	GEN









Measured in Full space (4π) conditions
Calculated maximum SPL based on rated power handling
AES standard, pink noise with 6 dB crest factor, free air.