





VRE-15G2

Specifications	The Vector VRE-15G2 is the ideal audio solution for users requiring a passive speaker system. With a power rating of 800W, the VRE-15G2 offers plenty of headroom when connected to a power amplifier. The twist lock input/output sockets ensure that cables are held securely when connected. All encased within a lightweight ABS moulded enclosure with 3 carry handles and 35mm pole stand socket.
Model	VRE-15G2
Description	VECTOR by HH VRE-15G2 - Passive moulded speaker - 800W - 15 inch LF + 1 inch CD
Power Rating	200W RMS, 800W Peak
Impedance	8 ohm
HF Driver	1" Compression Driver
LF Driver	15" Woofer
Sensitivity (1W/1M)	97
Coverage	90°H X 40°V
Enclosure	
Cabinet	Robust polypropylene cabinet with three handles and monitor angle
Finish	Black
Grille	Powdercoated steel, Black with acoustic foam backing
Other	35mm Distance Pole Socket
Unit dimensions (HWD)	69 x 44 x 37 CM 27.2" x 17.3" x 14.6"
Unit weight	11.5Kg, 25.4 lbs
Carton dimensions (HWD)	76.5 x 49.7 x 41 CM 30.1" x 19.6" x 16.1" , 0.156 M3
Packed weight	14.9Kg, 32.8 lbs
EAN Code	30.1" x 19.6" x 16.1", 0.156 M3 14.9Kg, 32.8 lbs 5060109456837









I Measured in Full space (4π) conditions 2 Calculated maximum SPL based on rated power handling 3 AES standard, pink noise with 6 dB crest factor, free air.