



2-Way 4-inch Coaxial Ceiling Loudspeaker

APT-C4

FEATURES

- Celestion 4-inch coaxial driver driver with 1.25-Inch LF VC and 0.75-inch HF VC.
- Custom horn flare profile designed in collaboration with Celestion.
- Lo-Z & 100v/70v operation via multi-tap transformer.
- Reversible dog ear mounts for thicker ceilings.
- Magnetic edge-to-edge grille with removable HH logo.
- Powder-coated steel back can with eyelet for safety tether.
- Optional black grille available.

APPLICATIONS

- Restaurants
- Bars
- Corporate facilities
- Retail
- Education



DESCRIPTION

The APT-C4 ceiling speaker brings decades of British design and engineering to installation audio. The APT-C4 harnesses a 4-inch Celestion coaxial driver, with a 1.25-inch LF voice coil and a 0.75-inch HF voice coil, enabling crystal-clear, well-balanced sound reproduction. The custom horn flare profile enhances audio clarity and provides well balanced, uniform sound throughout the coverage area.

The APT-C4 has a sensitivity of 87dB (1W/1M) and a 75W AES power rating, yielding a maximum SPL of 105dB SPL. Its frequency response of 90Hz to 20kHz ensures beautifully balanced audio, making it an excellent standalone solution or the perfect companion to the APT-C8S ceiling subwoofer or the APT-W8S surface-mount subwoofer for deeper bass extension.

The APT-C4 features a built-in multi-tap transformer suitable for use in both low-impedance (Lo-Z) and 100V/70V line applications.

Every detail of the APT-C4 is meticulously crafted to strike a perfect balance between aesthetic, acoustic, and mechanical design. Key features include:

- Magnetic edge-to-edge grille with a removable HH logo for seamless integration into any space.
- Reversible dog ear mounts, accommodating ceilings of various thicknesses.
- Powder-coated steel back can with an integrated safety tether eyelet for added security.
- Optional black grille for discreet installations in darker environments.

Whether in hospitality, corporate, commercial or educational settings, the APT-C4 ceiling speaker combines sophisticated engineering with elegant design, delivering uncompromising audio quality and reliability.





SPECIFICATIONS

| Model | APT-C4 |
|----------------------------|--|
| System type | 2-way Coaxial Ceiling Loudspeaker |
| Driver Specifications | Celestion 4-inch Coaxial Driver with 1.25-inch LF VC and 0.75-inch HF VC |
| 100V Power Options | 30W, 15W, 6W |
| 70V Power Options | 15W, 7.5W, 3W |
| Nominal System Impedance | 8 ohms |
| Power Rating | 75W AES, 150W Continuous, 300W Peak |
| Recommended Amplifier | MZ-140D, MZ-140Q, MZ-280Q |
| Sensitivity 1W/1m | 87dB |
| Maximum SPL (1m) | 105dB SPL, 111dB SPL (Peak) |
| Frequency Response | 90Hz-20kHz |
| Input / Link Connector | 4-pin Euroblock +/- +/- |
| Dispersion | 110° |
| Enclosure | |
| Main Construction Material | ABS/Steel |
| Finish | White ABS/Powdercoated Steel Back Can |
| Grille | White Fine Mesh Perforated Steel with Powdercoated Finish |
| Mounting Mechanism | 3 reversible dog leg mounts, safety tether eyelet. |
| Minimum Tile Thickness | 3mm |
| Maximum Tile Thickness | 65mm |
| Dimensions | |
| Cutout Diameter | 213mm |
| Outer Diameter | 248mm |
| Max Depth | 180.5mm |
| Optional Accessories | |
| | APT-TB4 - Tile bridge for APT-C4, APT-CG4-BK - Black Grille for APT-C4. |