

## APT-C8S

## 8-inch Ceiling Mount Subwoofer

### FEATURES

- 8-inch HH-Designed Low Frequency Driver.
- Integrated multi-tap transformer for Lo-Z & 100V/70V operation.
- Powder-coated steel backcan with integrated eyelet for safety tether.
- Magnetic edge-to-edge grille with removable HH logo.
- Optional black grille available.

### APPLICATIONS

- Bars
- Cafes
- Restaurants
- Retail
- Education
- Corporate facilities



### DESCRIPTION

The APT-C8S enhances the low-end performance of Aptur audio systems, providing a rich and immersive bass response that perfectly complements APT-C ceiling speakers and APT-P pendant speakers. Designed for background music applications, the APT-C8S brings full-bodied sound to any environment, offering bass extension that provides a well-balanced sonic accompaniment enhancing mood and atmosphere in bars, restaurants, cafes, retail environments, and beyond.

The APT-C8S features a built-in multi-tap transformer suitable for use in both low-impedance (Lo-Z) and 100V/70V line applications.

A focus on aesthetic, mechanical, and acoustic harmony has resulted in a thoughtfully designed subwoofer with features including:

- Magnetic edge-to-edge grille with a removable HH logo for sleek, unobtrusive integration.
- Reversible dog-ear mounts for compatibility with various ceiling thicknesses, ensuring effortless installation.
- A durable powder-coated steel back can with an integrated safety tether eyelet for additional safety.
- Optional black grille for discrete installation in darker environments.



## SPECIFICATIONS

Specifications	
Model	<i>APT-C8S</i>
System type	<i>Ceiling Mount Subwoofer</i>
Driver Specifications	<i>8-inch HH -Designed Low Frequency Driver</i>
100V Power Options	<i>100W, 50W, 25W, 13W</i>
70V Power Options	<i>100W, 50W, 25W, 13W, 6W</i>
Nominal System Impedance	<i>8 Ohms</i>
Power Rating	<i>100W AES, 200W Continuous, 400W Peak</i>
Recommended Amplifier	<i>MZ-140D, MZ-140Q, MZ-280Q</i>
Sensitivity 1W/1m	<i>89dB</i>
Maximum SPL (1m)	<i>109 dB SPL, 115dB SPL (Peak).</i>
Frequency Response	<i>40Hz-200Hz</i>
Input / Link Connector	<i>4-pin Euroblock +/- +/-</i>
<b>Enclosure</b>	
Main Construction Material	<i>ABS/Steel</i>
Finish	<i>White ABS/Powdercoated Steel Back Can</i>
Grille	<i>White Fine Mesh Perforated Steel with Powdercoated Finish</i>
Mounting Mechanism	<i>4 reversible dog leg mounts, safety tether eyelet.</i>
Minimum Tile Thickness	<i>3mm</i>
Maximum Tile Thickness	<i>65mm</i>
<b>Dimensions</b>	
Cutout Diameter	<i>298mm</i>
Outer Diameter	<i>333mm</i>
Max Depth	<i>207.5mm</i>
<b>Optional Accessories</b>	
	<i>APT-TB8 - Tile bridge for APT-C8(S), APT-CG8-BK - Black Grille for APT-C8(S).</i>

In the interest of continued development, HH reserves the right to amend product specification without prior notification.

