

APT-W8S

Single 8-inch Surface Mount Subwoofer

FEATURES

- 8-inch HH-Designed Low Frequency Driver.
- Integrated multi-tap transformer for Lo-Z & 100V/70V operation.
- Wall bracket included for simple installation.
- Slim profile to aid discrete integration.
- Rubber feet for freestanding installation.
- Available in Black or White.

APPLICATIONS

- Bars
- Restaurants
- Cafes
- Retail
- Education

DESCRIPTION

The APT-W8S enhances the low-end performance of Aptur audio systems, providing a rich and immersive bass response that perfectly complements APT-C ceiling speakers and APT-P pendant speakers. Designed for background music applications, the APT-W8S brings full-bodied sound to any environment, offering bass extension that provides a well-balanced sonic accompaniment enhancing mood and atmosphere in bars, restaurants, cafes, retail environments, and beyond.

The APT-W8S features a custom-designed HH LF driver with 89dB sensitivity and 100W AES power handling, yielding a maximum SPL of 109 dB. With a frequency response extending down to 40Hz, this slim and unobtrusive subwoofer ensures deep, resonant bass reproduction.

Built for flexibility, the APT-W8S features an integrated multi-tap transformer enabling use in Lo-Z and 70V/100V applications.

The APT-W8S slimline enclosure is thoughtfully designed for both form and function. The enclosure is appointed with rubber feet to provide stability as well as isolation from resonant surfaces while the included mounting bracket allows for discrete surface mounting to blend seamlessly into any environment or be hidden out of sight completely.

Whether for retail, hospitality, or corporate installations, the APT-W8S delivers exceptional bass performance with adaptability and ease.





Sub Enclosures

APTUR

Aptur Installation Loudspeakers

SPECIFICATIONS

Specifications	
Model	<i>APT-W8S</i>
System type	<i>Surface Mount Subwoofer</i>
Driver Specifications	<i>8-inch HH -Designed Low Frequency Driver</i>
100V Power Options	<i>100W, 50W, 25W, 13W</i>
70V Power Options	<i>100W, 50W, 25W, 13W, 6W</i>
Nominal System Impedance	<i>8 Ohms</i>
Power Rating	<i>100W AES, 200W Continuous, 400W Peak</i>
Recommended Amplifier	<i>MZ-140D, MZ-140Q, MZ-280Q</i>
Sensitivity 1W/1m	<i>89dB</i>
Maximum SPL (1m)	<i>109 dB SPL, 115dB SPL (Peak).</i>
Frequency Response	<i>40Hz-200Hz</i>
Input / Link Connector	<i>4-pin Euroblock +/- +/-</i>
Enclosure	
Main Construction Material	<i>Plywood</i>
Finish	<i>Black/White Paint</i>
Grille	<i>Black/White Fine Mesh Perforated Steel with Powdercoated Finish</i>
Mounting Bracket	<i>Steel surface mount bracket included.</i>
Dimensions	
With Feet (HWD)	<i>327mm x 520mm x 175mm</i>
Without Feet (HWD)	<i>320mm x 520mm x 168mm</i>
Wall Clearance with Bracket	<i>10mm</i>
Optional Accessories	
	<i>NA</i>

In the interest of continued development, HH reserves the right to amend product specification without prior notification.

