

## S15-H

15" Passive Subwoofer

### FEATURES

- 15" low-frequency driver.
- 134dB Max SPL (Peak).
- Frequency Response of 50Hz - 180Hz ( $\pm 3$ dB).
- Maintains low distortion under high-power conditions.
- Integrated 3-point rigging system
- Hard wearing paint finish.

### APPLICATIONS

- Small to medium sized theatres
- Small to medium sized live music venues
- Corporate AV Events
- Fixed installations in concert halls, ballrooms and houses of worship.



### DESCRIPTION

The S15-H passive subwoofer comprises a single 15" low frequency driver reinforced with a nano coating. The driver diaphragm has a better rigidity allowing the unit to maintain low distortion and continuous energy output under high-power conditions.

The S15 provides a maximum SPL of 134dB (Peak).

The 520mm wide enclosure is designed to pair seamlessly with the LA8D 2 x 8" Line Array Enclosure via the integrated 3-point rigging system. The 30KG cabinet features 4 side handles and provision for castors to improve portability. The S15-H constructed of acoustically optimised plywood with extensive internal bracing, finished with hard wearing black paint and appointed with a hexagonal mesh black perforated steel grille with acoustic foam backing.



Specifications

<b>Specifications</b>	
System type	15" Passive Subwoofer
Frequency Response	50Hz-180Hz(±3dB)
	40Hz-400Hz(-10dB)
Power Rating	600W Continuous, 2400W Peak
Maximum SPL	128dB Continuous, 134dB Peak
Sensitivity	100dB(1W@1m)
Nominal Impedance	8 Ohms
<b>Speaker</b>	
LF Driver	1 x 15" low-frequency driver
<b>Enclosure</b>	
Cabinet	Plywood
Finish	Hard-wearing black paint
Grille	Hexagonal mesh perforated steel with acoustic foam backing.
Fittings	4 x Side handles. Provision for castors.
Mounting Bracket	S15-FLB for suspended mounting
<b>Connect</b>	
Connectors	2 x Speakon NL4
Pin Connections (Input)	1+/-
Pin Connections (Link)	1+/- and 2+/-
Dimensions (H/W/D)	430×520×600mm
Weight	30kg



DIMENSIONS

