

S18

18" Passive Subwoofer

FEATURES

- 18" low-frequency driver.
- 136dB Max SPL (Peak).
- Frequency Response of 40Hz - 260Hz (± 3 dB).
- Maintains low distortion under high-power conditions.
- Hard wearing paint finish.

APPLICATIONS

- Concert halls
- Theatres
- Houses of Worship
- Clubs and bars
- Small to medium size music venues.
- Conference spaces



DESCRIPTION

The S18 passive subwoofer comprises a single 18" low frequency driver reinforced with a nano coating. The driver diaphragm has a better rigidity allowing the unit to maintain low distortion and continuous energy output under high-power conditions.

The S18 provides a maximum SPL of 136dB (Peak).

The 44KG cabinet features 4 side handles and provision for castors to improve portability. The S18 constructed of acoustically optimised plywood with extensive internal bracing, finished with hard wearing black paint and appointed with a hexagonal mesh black perforated steel grille with acoustic foam backing.



Specifications

Specifications	
System type	18" Passive Subwoofer
Frequency Response	40Hz-260Hz(±3dB) 35Hz-300Hz(-10dB)
Power Rating	900W Continuous, 3600W Peak
Maximum SPL	130dB Continuous, 136dB Peak
Sensitivity	102dB(1W@1m)
Nominal Impedance	8 Ohms
Speaker	
LF Driver	1 x 18" low-frequency driver
Enclosure	
Cabinet	Plywood
Finish	Hard-wearing black paint.
Grille	Hexagonal mesh black perforated steel with acoustic foam backing.
Fittings	4 x Side handles, provision for castors
Connect	
Connectors	2 x Speakon NL4
Pin Connections (Input)	1+/-
Pin Connections (Link)	1+/- and 2+/-
Dimensions (H/W/D)	550×710×750mm
Weight	44kg



DIMENSIONS

